

THANK YOU

Thank you for purchasing our FerroForcia parts!

PACKAGE CONTENT

Part number	Quantity	Description
HSS2-001-U	1	1x left mirror hinge 1x left hinge 1x right mirror hinge 1x right hinge 4x hinge pin 8x hinge ring 4x grease nipple 4x blind cap 4x M6x16 allen screw

PAINTING/ASSEMBLY LIST

Before painting and mounting the hinges onto your Defender, first check the instructions as described in our [Painting/Assembly list](#).

MOUNTING VIDEO

Besides the mounting instruction below, we also have a mounting video available. Scan the QR-code or go to our website www.ferroforcia.com/product/hss2-001-u/



MOUNTING INSTRUCTION

Replace the side-door hinges door by door.

- 1 Start by disassembling the upper hinge (with mirror attached).
- 2 Disassemble the mirror from the old hinge.
- 3 Assemble mirror onto the FerroForcia hinge with the two extra holes, using the M6x16 screws. Make sure it's tightly secured.
- 4 Clean the spot on the door where the hinge will be mounted.
- 5 Mount hinge with mirror onto the door
 - a) Make use of filler plate(s) between the hinge and door if the sheet metal doesn't connect nicely
 - b) Turn 2 screws that go into the frame
 - c) Now turn the 2 screws that connects the hinge directly with the door. Make sure to hold the sheet metal straight during mounting
 - d) Check if the door fits nicely
- 6 Move on with the lower hinge on the same door.
- 7 Disassemble the old hinge.
- 8 Clean the spot on the door where the hinge will be mounted.
- 9 Mount new hinge onto the door
 - a) Make use of filler plate(s) between the hinge and door if the sheet metal doesn't connect nicely
 - b) Turn 2 screws that go into the frame
 - c) Now turn the 2 screws that connects the hinge directly with the door. Make sure to hold the sheet metal straight during mounting
 - d) Check if the door fits nicely
- 10 Make sure all screws, of the upper and lower hinge, are tightly secured when the sheet metal connects nicely.
- 11 Repeat all steps 1-10 for the other door.
- 12 If you prefer, you can replace the grease nipples with the blind caps which are included. Make sure to keep the grease nipples, for when you need to grease again!