

THANK YOU

Thank you for purchasing our FerroForcia parts!

PACKAGE CONTENT

Part number	Quantity	Description
HSS4-001	1	1x left mirror hinge 3x left hinge 1x right mirror hinge 3x right hinge 8x blind cap 4x M6x16 allen screw

MOUNTING VIDEO

Besides the mounting instruction below, we also have a mounting video available. Scan the QR-code or go to our website www.ferroforcia.com/product/hss4-001/



MOUNTING INSTRUCTION

Replace the side-door hinges door by door.

Door with mirror

- 1 Start by disassembling the upper hinge (with mirror attached).
- 2 Disassemble the mirror from the old hinge.
- 3 Assemble the mirror onto the FerroForcia hinge with the two extra holes. Make sure it's tightly secured.
- 4 Clean the spot on the door where the hinge will be mounted.

- 5 Mount the hinge with mirror onto the door
 - a) Make use of filler plate(s) between the hinge and door if the sheet metal doesn't connect nicely
 - b) First turn the 2 screws that go into the frame
 - c) Check if the door fits nicely
 - d) Now turn the 2 screws that connects the hinge directly with the door. Make sure to hold the sheet metal straight during mounting

- 6 Move on with the lower hinge on the same door.

- 7 Disassemble the old hinge.

- 8 Clean the spot on the door where the hinge will be mounted.

- 9 Mount the FerroForcia hinge onto the door

- a) Make use of filler plate(s) between the hinge and door if the sheet metal doesn't connect nicely
- b) First turn the 2 screws that go into the frame
- c) Check if the door fits nicely
- d) Now turn the 2 screws that connects the hinge directly with the door. Make sure to hold the sheet metal straight during mounting

- 10 Make sure all screws, of the upper and lower hinge, are tightly secured when the sheet metal connects nicely.

- 11 Repeat all steps 1-10 for the other door with mirror.

Door without mirror

- 12 Start by disassembling the upper hinge.
- 13 Disassemble the old hinge.
- 14 Clean the spot on the door where the hinge will be mounted

- 15** Mount the FerroForcia hinge onto the door
 - a)** Make use of filler plate(s) between the hinge and door if the sheet metal doesn't connect nicely
 - b)** First turn the 2 screws that go into the frame
 - c)** Check if the door fits nicely
 - d)** Now turn the 2 screws that connects the hinge directly with the door. Make sure to hold the sheet metal straight during mounting

- 16** Move on with the lower hinge on the same door.

- 17** Disassemble the old hinge.

- 18** Clean the spot on the door where the hinge will be mounted.

- 19** Mount the FerroForcia hinge onto the door
 - a)** Make use of filler plate(s) between the hinge and door if the sheet metal doesn't connect nicely
 - b)** First turn the 2 screws that go into the frame
 - c)** Check if the door fits nicely
 - d)** Now turn the 2 screws that connects the hinge directly with the door. Make sure to hold the sheet metal straight during mounting

- 20** Make sure all screws, of the upper and lower hinge, are tightly secured when the sheet metal connects nicely.

- 21** Repeat all steps 12-20 for the other door with mirror.

- 22** If you prefer, you can replace the grease nipples with the blind caps which are included. Make sure to keep the grease nipples, for when you need to grease again!